

TECHNISCHE EIGENSCHAPPEN
TUTELA TRANSMISSION STARGEAR AX
ARTIKELCODE: 2292

TOEPASSING

Lubricant for axles of cars and commercial vehicles (especially the Mercedes) that allows for maximum protection of the mechanical parts during use at high temperatures and severe operating conditions.

The modern formulation ensures protection against wear, oxidation and rust.
 The viscometric index allows rapid and safe lubrication during cold starts and during exercise at low temperatures.

SPECIFICATIES

SAE 85W-90, API GL 5, MB-Approval 235.0, RENAULT where API GL5 Recommended

ZF TE-ML 16C, ZF TE-ML 17B, ZF TE-ML 19B, ZF TE-ML 21A, MAN 342 Type_M1 Performance, MIL-L-2105 D

OMSCHRIJVING TEST

OMSCHRIJVING TEST	METHODE	EENHEID	TYPISCHE WAARDE
VOORKOMEN	--	--	B&C
KLEUR	--	--	AMBER
DENSITEIT @ 15°C	ASTM D 4052	g/cm ³	0.900
VISCOSITEIT @ 100°C	ASTM D 445	cSt	17
VISCOSITEIT @ 40°C	ASTM D 445	cSt	189
VISCOSITEITINDEX	ASTM D 2270	--	95
VISCOSITEIT @ -12°C	ASTM D 2983	cPs	31000
STOLPUNT	ASTM D 97	°C	-30
VLAMPUNT CI. O. C.	ASTM D 92	°C	215
SCHUIM @ 24°C	ASTM D 892	cc/s	TRACES/0

Alle technische informatie wordt als referentie gegeven.