



PETRONAS

PROPRIETES TECHNIQUES

TUTELA TRANSMISSION AS8

CODE DU PRODUIT: 2315

EMPLOI

Tutela T. AS8 is a synthetic heavy-duty oil, developed specifically for ZF's automatic 5/6/8-speed transmissions. Tutela T. AS8 guarantees maximum performance of the automatic transmission ensuring minimal level of wear.

SPECIFICATION

FIAT 9.55550-AV5 CTR N°F139.I11

, MS-90030-A5, ZF-TE-ML-11

TEST

DESCRIPTION DU TEST	METHODE	UNITE DE MESURE	VALEUR TYPIQUE
ASPECT	--	--	B&C
COULEUR	--	--	GREEN
DENSITE A 15°C	ASTM D 4052	g/cm ³	0,845
VISCOSITE A 100°C	ASTM D 445	cSt	5,6
VISCOSITE A 40°C	ASTM D 445	cSt	24,9
POINT D'ÉCOULEMENT	ASTM D 97	°C	-45
POINT D'ÉCLAIR DE CLEVELAND (CUVETTE OUVERTE)	ASTM D 92	°C	206
VISCOSITE A 100°C APRES KRL 20H	ASTM D 445	cST	5,3

Les données présentes dans cette fiche de sécurité ne constituent pas une spécification et elles sont soumises aux tolérances normales de production.

DEVELOPPEMENT PRODUIT

12/2016