



TECHNICAL DATA SHEET

SVITOL PROFESSIONAL LITHIUM LUBRICANT

- **PRODUCT DESCRIPTION**

Multipurpose grease based on a soap compound of lithium and highly refined mineral oil. Indispensable for protecting against wear, corrosion and rust. It leaves a thin lubricating protective film. High resistance to centrifugation, very resistant to run-off, steam and cold. Contains anticorrosion, tackifier and anti-oxidizing agents. It adheres to all materials and offers a thorough lubrication. Resistant to weak acids and diluted hydroxides. It does not contain acids and can be used on all types of plastic (a compatibility test is always to be recommended, however).

- **FIELDS OF USE**

Suitable for the automotive industry, it can be used for bearings, wheel hubs. Excellent for gears, pulleys, guide rails, up-and-over doors, winches, hinges, fans, blades, pneumatic and electrical tools.

It can be used in the industrial and marine sectors for the widest range of lubrication problems; hinges, locks and mechanisms of various types, especially the moving parts of vehicles.

- **METHOD OF USE**

Shake the can well. Spray directly on the surface to be treated from a distance of 15 – 30 cm.

The product can even be dispensed with the can upside down.

- **STORAGE**

Product validity in sealed packaging and stored at room temperature: at least 3 years

- **PACKAGING**

Spray bottle
Code 4121 400 ml

- **NOTES**

For information on product safety, please consult the safety sheet.

R&D 23 September 2015

Property	Unit of measurement	Typical values
• Appearance		Creamy
• Color		clear
• Odor		Typical
• Specific weight	Kg/l	approx. 0.650
• Propellant		Propane/Butane
• NLGI grade		1 - 2
• Worked penetration		308 – 320
• Dropping point	°C	>300
• Operating temperature	°C	-20 +160
• Weld load IP 239	Kg	320
• First mesh load IP 239	Kg	120

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user.
For information, please contact our Technical Dept. on no. 800-016604

REGISTERED OFFICE:
VIA SANTENA, 1 – 10029 VILLASTELLONE (TO) ITALY
COMP.CAP. € 20,010,000.00 F.P. — VAT CODE 0508275068
TAX CODE 05082750968
TURIN REGISTER OF BUSINESSES 05082750968
TURIN REGISTER OF BUSINESSES & CRAFTS 1051229
COORDINATION MANAGEMENT EX ART.2497 C.C.
PLI (NETHERLANDS) B.V.
A wholly-owned subsidiary of PETRONAS

OFFICES AND PRODUCTION PLANT
VIA ANTICA DI CASSANO, 23
20063 CERNUSCO SUL NAVIGLIO (MI) ITALY
CALL CENTER 02 92436.1
FAX 02 92436306
WWW.AREXONS.IT

